

**MODEL AVAILABILITY**

Drive	Body Style	Payload, lbs.(b) lbs.(c)	GVWR, lbs.(a)	Price Class	Estimated	Estimated	
					Standard	Curb Weight,	
				Engine and Transmission			
2WD	Regular Cab	3641	5000	Base, Sport, SLT	3.9L V-6 and five-speed manual		
				Sport, SLT	4.7L V-8 and five-speed manual	3692	
				Sport(d)	5.9L V-8 and four-speed automatic		
		1310	5900(e)	Base, Sport, SLT	3.9L V-6 and five-speed		
					Sport, SLT	4.7L V-8 and five-speed manual	3793
					Sport(e)	5.9L V-8 and four-speed automatic	
	Club Cab®	3743	5350	Base, Sport, SLT	3.9L V-6 and five-speed		
				Sport, SLT	4.7L V-8 and five-speed manual	3908	
				Sport(e)	5.9L V-8 and four-speed automatic		
		2110	5900(e)	Base, Sport, SLT	3.9L V-6 and five-speed		
					Sport, SLT	4.7L V-8 and five-speed manual	3992
					Sport(e)	5.9L V-8 and four-speed automatic	
4WD	Regular Cab	3959	5400	Base, Sport, SLT	3.9L V-6 and five-speed manual		
				Sport, SLT	4.7L V-8 and five-speed manual	4297	
				Sport, SLT	5.9L V-8 and four-speed automatic		
	1440	5900(e)	Base, Sport, SLT	3.9L V-6 and five-speed			
				Sport, SLT	4.7L V-8 and five-speed manual	4042	
				Sport(e)	5.9L V-8 and four-speed automatic		
Quad Cab™	4244	6010	Sport, SLT	3.9L V-6 and five-speed manual			
			Sport, SLT	4.7L V-8 and five-speed manual	4180		
			Sport, SLT	5.9L V-8 and four-speed automatic			
	1710	5900(e)	Base, Sport, SLT	3.9L V-6 and five-speed			
				Sport, SLT	4.7L V-8 and five-speed manual	4180	
				Sport(e)	5.9L V-8 and four-speed automatic		
4WD	Regular Cab	4105	5400	Base, Sport, SLT	3.9L V-6 and five-speed manual		
				Sport, SLT	4.7L V-8 and five-speed manual	4180	
				Sport, SLT	5.9L V-8 and four-speed automatic		
	1420	5900(e)	Base, Sport, SLT	3.9L V-6 and five-speed			
				Sport, SLT	4.7L V-8 and five-speed manual	4180	
				Sport(e)	5.9L V-8 and four-speed automatic		

manual	4142	5900(e) 1760	Base, Sport, SLT	3.9L V-6 and five-speed	
	1680		Sport, SLT	4.7L V-8 and five-speed manual	4219
	4484	Quad Cab 1530	Sport, SLT	3.9L V-6 and five-speed manual	
	1480		Sport, SLT	4.7L V-8 and five-speed manual	4531
	1330		Sport, SLT	5.9L V-8 and four-speed automatic	4683

- (a) Gross Vehicle Weight Rating.
- (b) Weight shown is for base model with standard equipment.
- (c) Payload represents maximum allowable weight of driver, passengers and cargo. It is reduced by optional equipment weight.
- (d) Must have R/T Group.
- (e) Optional.

**POWERTRAIN AVAILABILITY**

**REGULAR CAB**

**2WD**

GVWR, lbs.	Engine Axle Ratio(a) V-6 3.21	Manual Transmission			Automatic Transmission							
		3.9L V-8 3.55	4.7L V-8 3.92	5.9L Five-Speed	NV3500 Four-Speed	42RE Four-Speed	46RE Four-Speed	5-45RFE Five-Speed				
Base												
5000	S	—	—	S	—	—	—	—	S(b)	O		
		S	—	—	—	O	—	—	—	—	S	O
5900	S	—	—	S	—	—	—	—	—	S(d)	—	
	S	—	—	—	O	—	—	—	—	—	O	
Sport												
5000	—	—	O(c)	—	—	O	—	—	—	—	S(b)	
		O	—	—	S	—	—	—	—	S(b)	O	
		O	—	—	—	O	—	—	—	—	S	O
		—	O	—	S	—	—	—	—	—	S	O
		—	O	—	—	—	—	—	O	—	S	O
5900	O	—	—	S	—	—	—	—	—	S(d)		
		O	—	—	—	O	—	—	—	—	—	S(d)
		—	O	—	S	—	—	—	—	—	S	O
	—	O	—	—	—	—	O	—	—	S(d)	O(d)	
SLT												
5000	S	—	—	S	—	—	—	—	—	S(b)	O	
		S	—	—	—	O	—	—	—	—	S	O
		—	O	—	S	—	—	—	—	—	S	O(d)
		—	O	—	—	—	—	O	—	—	S	O(d)
5900	S	—	—	S	—	—	—	—	—	S(d)		
		S	—	—	—	O	—	—	—	—	—	S(d)
		—	O	—	S	—	—	—	—	—	S	O
	—	O	—	—	—	—	O	—	—	S(d)	O(d)	

Legend: S = Standard O = Optional — = Not Available

(a) Anti-spin differential optional except where noted.

(b) Anti-spin differential not available.

(c) Must have R/T Group.

(d) Anti-spin differential standard.

**POWERTRAIN AVAILABILITY**

**REGULAR CAB**

**4WD**

GVWR, lbs.	Engine Axle Ratio(a)	Manual Transmission			Automatic Transmission						
		3.9L V-8	4.7L V-8	5.9L V-8	NV3500 Five-Speed	42RE Four-Speed	46RE Four-Speed	5-45RFE Five-Speed			
		3.21	3.55	3.92							
Base											
5400	S	—	—	—	—	—	—	—	S	O	—
		S	—	—	—	—	—	O	—	S	—
5900	S	—	—	—	—	—	—	—	S	O	—
	S	—	—	—	—	—	O	—	—	S	—
Sport											
5400	S	—	—	—	—	—	—	—	S	O	—
		S	—	—	O	—	—	—	—	—	S
		—	O	—	—	—	—	—	—	S	O(b)
		—	O	—	—	—	—	O	—	S	O(b)
		—	O	—	—	—	—	O	—	S	O
5900	S	—	—	—	—	—	—	—	S	O	—
	S	—	—	—	O	—	—	—	—	—	S
		—	O	—	—	—	—	—	—	S	O(b)
		—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O	—
SLT											
5400	S	—	—	—	—	—	—	—	S	O	—
		S	—	—	O	—	—	—	—	—	S
		—	O	—	—	—	—	—	—	S	O(b)
		—	O	—	—	—	—	O	—	S	O(b)
		—	O	—	—	—	—	O	—	S	O
5900	S	—	—	—	—	—	—	—	S	O	—
	S	—	—	—	O	—	—	—	—	—	S
		—	—	—	—	—	—	S	—	—	O(b)
		—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O	—

(a) Anti-spin differential optional except where noted.

(b) Anti-spin differential standard.

**POWERTRAIN AVAILABILITY**

**CLUB CAB®  
2WD**

GVWR, lbs.	Engine Axle Ratio(a)	Manual Transmission			Automatic Transmission						
		3.9L V-6	4.7L V-8	5.9L V-8	NV3500 Five-Speed	42RE Four-Speed	46RE Four-Speed	5-45RFE Five-Speed			
		3.21	3.55	3.92							
Base											
5350	O	—	—	S	—	—	—	S(b)	O		
		O	—	—	—	O	—	—	—	S	O
6010(e)		O	—	—	S	—	—	—	—	S(c)	
	O	—	—	—	O	—	—	—	—	S(c)	
Sport		—	—	—	—	—	—	—	—	—	
		—	—	O(d)	—	—	O	—	—	—	S(c)
5350	O	—	—	S	—	—	—	S(b)	O		
		O	—	—	—	O	—	—	—	S	O
		—	O	—	S	—	—	—	—	S	O
		—	O	—	—	—	—	—	—	S	O
6010(e)		O	—	—	S	—	—	O	—	S(c)	
		O	—	—	—	O	—	—	—	—	S(c)
	—	O	—	—	—	—	O	—	S(c)	O(c)	
SLT											
5350	S	—	—	S	—	—	—	S(b)	O		
		S	—	—	—	O	—	—	—	S	O
		—	O	—	S	—	—	—	—	S	O
		—	O	—	—	—	—	O	—	S	O
6010(e)		S	—	—	S	—	—	—	—	S(c)	
		S	—	—	—	O	—	—	—	—	S(c)
		—	O	—	S	—	—	—	—	S	O
	—	O	—	—	—	—	O	—	S(c)	O(c)	

(a) Anti-spin differential optional except where noted.

(b) Anti-spin differential not available.

(c) Anti-spin differential standard.

(d) Must have R/T Group.

(e) Except in California.

**POWERTRAIN AVAILABILITY**

**CLUB CAB®  
4WD**

GVWR, lbs.	Engine			Manual Transmission		Automatic Transmission			S	O
	Axle Ratio(a)			NV3500 Five-Speed	42RE Four-Speed	46RE Four-Speed	5-45RFE Five-Speed			
	V-6 3.21	V-8 3.55	V-8 3.92							
Base 6010(c)	S	—	—	S	—	—	—	—	S	O
	S	—	—	—	O	—	—	—	—	S
	S	—	—	S	—	—	—	—	S	O
S	—	—	—	O	—	—	—	—	S	
Sport 6010(c)	S	—	—	S	—	—	—	—	S	O
	S	—	—	—	O	—	—	—	—	S
	—	O	—	S	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	—	—	S	O
	S	—	—	S	—	—	—	—	S	O
	S	—	—	—	O	—	—	—	—	S
	—	O	—	S	—	—	—	—	S(b)	O(b)
	—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O
SLT 6010(c)	S	—	—	S	—	—	—	—	S	O
	S	—	—	—	O	—	—	—	—	S
	—	O	—	S	—	—	—	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O
	S	—	—	S	—	—	—	—	S	O
	S	—	—	—	O	—	—	—	—	S
	—	O	—	S	—	—	—	—	S(b)	O(b)
	—	O	—	—	—	—	O	—	S	O(b)
	—	O	—	—	—	—	O	—	S	O

(a) Anti-spin differential optional except where noted.

(b) Anti-spin differential standard.

(c) Except in California.

**POWERTRAIN AVAILABILITY**

**QUAD CAB™  
2WD**

GVWR, lbs.	Engine Axle Ratio(a)	Manual Transmission			Automatic Transmission						
		3.9L V-6	4.7L V-8	5.9L V-8	NV3500 Five-Speed	42RE Four-Speed	46RE Four-Speed	5-45RFE Five-Speed			
		3.21	3.55	3.92							
Sport 6010	S	—	—	S	—	—	—	—	S	O	
		S	—	—	—	O	—	—	—	S	O
		—	O	—	S	—	—	—	—	S	O
		—	O	—	—	—	—	O	—	S	O
		—	—	O	—	—	O	—	—	S	O
SLT		S	—	—	S	—	—	—	—	S	O
		S	—	—	—	O	—	—	—	S	O
		—	O	—	S	—	—	—	—	S	O
	—	O	—	—	—	—	O	—	S	O	
<b>4WD</b>											
Sport and SLT											
Sport 6010	S	—	—	S	—	—	—	—	S	O	
		S	—	—	—	O	—	—	—	S	O
		—	O	—	S	—	—	—	—	S	O
		—	O	—	—	—	—	O	—	S	O
		—	O	—	—	—	—	O	—	S	O
		—	—	O	—	—	O	—	—	S	O
	—	—	O	—	—	O	—	—	S	O	

(a) Anti-spin differential optional.

## REGULAR CAB FEATURE AVAILABILITY

Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T(a)				
<b>EXTERIOR</b>										
Box Bedliner	—	Under rail		O	O	O	O	O	O	O
Bumpers										
Front										
		Chrome		—	—	—	—	S	S	—
		Body color/Black		—	—	S	S	—	—	—
		Body color (included in optional Ground Effects Group)			—	—	P	P	—	—
	S	Gray	S	S	—	—	—	—	—	—
Rear with Step Pads										
		Chrome		—	—	—	—	S	S	—
		Painted Black with body color inserts						—	—	S
	S	—	—	—						
		Body color (included in optional Group Effects Group)			—	—	P	P	—	—
	—	S								
		Painted Black with Gray inserts				S	S	—	—	—
	—	—	—							
Colors										
		Atlantic Blue Pearl Coat, Black, Bright Silver Metallic, Bright White, Flame Red, Graphite Metallic, and Patriot Blue Pearl Coat								
	O	O				O	O	O	O	O
		Dark Garnet Red Pearl Coat and Light Almond Pearl Coat Metallic								
		O	O	—	—	O	O	—	—	—
Fascias, Front — Painted										
		Body Color	—	—	S	S	—	—	S	—
		Low-Gloss Gray		—	—	—	—	S	S	—
		Graphite Metallic	S	S	—	—	—	—	—	—
Fog Lamps (must have Light Group)										
	S	S				—	—	O	S	O
Glass — Tinted, all										
		S	S	S	S	S	S	S	S	—
Grille										
		Painted (Gray)		S	—	—	—	—	—	—
		Painted (body color)		—	S	S	S	—	—	S
		Chrome		—	—	—	—	S	S	—
Mirrors (Black)										
		Dual 5" x 7", Manual			S	S	S	—	S	—
	S									
		Dual 5" x 7", Power (included in Power Convenience Group)			—	—	—	S	—	S
		Dual 6" x 9", folding power heated								O

(must have Power Convenience Group) — — — O —  
 O O

Moldings

Side (Black) — — — — O O —  
 Windshield (Black) S S S S S S S

Legend: S = Standard O = Optional P = Available within package or group  
 noted in parentheses

O/P = Item is a freestanding option and also included in package or group as  
 noted — = Not available.

NOTE: The information shown is preliminary and based on data available at the  
 time of publication.

(a) Two-wheel drive models only.

## REGULAR CAB FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T(a)
<b>EXTERIOR (continued)</b>							
Paint Treatment							
Monotone			S	S	S	S	S
Two-tone, lower accent color (Bright Silver)						—	—
O	O	—					
Rear Window — Sliding			O	O	O	O	O
Tonneau Cover — Soft			O	O	O	O	O
Wheel flares							
Body color (included in Tire and Handling Group)			—	P	—	P	S
Graphite Metallic (included in Tire and Handling Group)			—	—	—	—	—
Windshield Wipers — Variable-delay intermittent						S	S
S	S	S	S				S
<b>INTERIOR</b>							
Assist Handles, Driver and passenger					S	S	S
S	S						S
Cigar Lighter							
(Smoker's Package available through Mopar)						O	O
O	O	O	O				O
Climate Control — Air conditioning					S	S	S
S	S						S
Colors							
Dark Slate Gray				S	S	O	O
Taupe		—	—	O	O	S	S
Dome Lamp		S	S	S	S	S	S
Floor Covering							
Vinyl (Black)			S	—	—	—	—
Carpet — Front seat area			—	S	S	S	S
Floor Mats — Front, carpeted (color-keyed)						—	—
O	S	O					S
Instrument Cluster							
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission), odometer and trip odometer			S	S	S	S	S
Gauges, analog: oil pressure, temperature, voltmeter, tachometer, 110-mph (180-kph) speedometer, fuel							—
S	S	S	S				S

(a) Two-wheel drive models only.

## REGULAR CAB FEATURE AVAILABILITY

### Base SXT Sport Sport Plus SLT SLT Plus R/T INTERIOR (continued)

Gauges, analog: temperature, tachometer, 110-mph (180-kph) speedometer, fuel

	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T
Gauges, analog: temperature, tachometer, 110-mph (180-kph) speedometer, fuel	S	S	—	—	—	—
Mirror — Rearview, manual day/night	—	—	—	—	S	S S S S
Power Outlet (located in instrument panel)	S	S	S	—	—	S S S S

#### Seat and Door Trim

Yosemite cloth seats and Miller vinyl door trim bolsters	—	—	S	S	—	—	—	—
Yosemite cloth seats and door trim panel bolsters; door map pockets (color-keyed)	—	—	—	—	—	S	S	S S

#### Seats

40/20/40 split bench with recliners and integral head restraints, right and left; center armrest console with storage (includes floor console with two cup holders and storage bins; optional with R/T Group)	S	S	O	—	—	S	—	S S
Reclining high-back bucket (includes floor console with armrest, covered storage with removable cassette/CD tray, pen holder, coin holder, three cup holders, cellular telephone compartment, internal power outlet and lamp)	O	O	O	O	S	—	—	S

#### Sound Systems

AM/FM stereo radio with cassette and four speakers	S	—	S	—	S	—	—	S —
AM/FM stereo radio with cassette, CD, three-band equalizer, 120-watt amplifier with eight Infinity® speakers in six locations	—	—	—	—	O	O	O	O O
AM/FM stereo radio with CD, changer controls, bass and treble controls, 120-watt amplifier with eight Infinity speakers in six locations	—	—	—	—	S	O	S	O S O
AM/FM stereo radio with in-dash six-disc CD, changer controls, bass and treble controls, 120-watt amplifier with eight Infinity speakers in six locations (late availability)	O	O	O	O	—	—	—	O

Audio controls — Steering wheel-mounted, six-function (must have Power Convenience Group, AM/FM stereo radio with cassette and CD and leather-wrapped steering wheel)	—	—	—	—	O	—	O	O
Steering Column — Tilt	—	—	—	O	—	S	—	S S

## REGULAR CAB FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T		
<b>INTERIOR (continued)</b>									
Steering Wheel									
Luxury			S	S	S	S	S	—	
Leather-wrapped (must have Deluxe Convenience Group; included in R/T Group)				—	—	—	O	—	O S
Sun Visors — Padded cloth with mirror, right (color-keyed)									S S
	S	S	S	S	S				
<b>POWERTRAIN and CHASSIS</b>									
Brakes, Power									
Power front disc and rear drum with rear wheel anti-lock (included on 2WD models under 5400 lbs. GVWR)								S	S S
	S	S	S	—					
Power four-wheel disc with rear wheel anti-lock (included on all 4WD models and 2WD models over 5400 lbs. GVWR)			S	—	S	S	S	S	
Power anti-lock four-wheel anti-lock four-wheel disc									O O
	O	O	O	O	O	O	O		
Engine Cooling — Heavy-duty (includes power steering cooler and auxiliary transmission oil cooler with automatic transmission)			O	O	O	O	O	O	
Heater — Engine Block					O	O	O	O	O O
Tires(a)									
P245/70R16 black sidewall all-season							S	S	S —
	S	—	—						
P245/70R16 outline white letter on-off road								—	— —
	S	—	S	—					
P255/55R17 outline white letter						—	—	—	— —
	—	S							
P255/55R16 outline white letter all-terrain (included in 2WD Tire and Handling Group)							—	S	P O
	P	O	—						
P265/70R16 outline white letter all-terrain (included in 4WD Tire and Handling Group)							—	S	P O
	P	O	—						
Spare, conventional				S	S	S	S	S	S S
Transfer Cases									
NV233HD Electric-shift part-time (4WD only)								S	S S
	S	S	S	—					
NV244HD Electric-shift full-time (4WD only; must have 4.7L or 5.9L engine)					—	—	O	O	O O —

(a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.

## REGULAR CAB FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T
<b>POWERTRAIN and CHASSIS (continued)</b>							
Wheels							
Styled steel, 16" x 7" painted	—	—			S	—	—
Cast-aluminum, 16" x 7"	—	—		—	—	S	—
Cast-aluminum, 16" x 8" (included in Tire and Handling Groups)	S	—			—	P	P
Cast-aluminum, chrome 17" x 9"	—	S			—	—	—

## SAFETY and SECURITY

Brake-Shift Interlock (included with automatic transmission)	S	S	S	S	S	S	S
Passenger Air Bag On/Off Switch(a)	S	S			S	S	S
Restraints							
Air Bags: Next-generation front (driver and passenger) with knee bolsters(b)	S	S	S			S	S
Seat Belts: Height-adjustable three-point seat belts, outboard; lap belt, center	S	S			S	S	S
Security Alarm (includes Sentry Key® engine immobilizer; requires Power Convenience Group)	O	—	O	O			—
User-Ready Child Seat Tether Anchors—Top, cab back (three)	S	S	S	S	S	S	S
Child Seat Anchor System — Lower Anchors and upper Tethers for Children (LATCH)	S	S			S	S	S
Constant Force Retractors (driver)	S	S			S	S	S
Interior Upper Head Impact Protection — Front driver and passenger; meets 2003 federal standard	S	S			S	S	S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

(b) Important, always remove key and replace cover. A rearward facing child seat may be used in the front passenger seat only with the air bag turned off.

## REGULAR CAB FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T		
<b>EQUIPMENT GROUPS</b>									
Deluxe Convenience Group — Automatic speed control and tilt steering column			—	P	—	P	—	P	S
Ground Effects Group (Stampede) — Front fascia extension, rocker cladding from front fender to rear of box, body color front fascia, body color rear bumper,									
Tire and Handling Group			—	—	O	O	—	—	—
GVW Rating — 6010(b) pounds (not available with Tire and Handling Group, R/T Group, Sport Plus Group or SLT Plus Group)			O	—	O	—	O	—	—
Heavy-Duty Service Group — 136-amp alternator, 750-amp battery and heavy-duty engine cooling			O	O			O	O	O
Power Convenience Group — Power mirrors, remote keyless entry system, power front windows with driver one-touch open and power door locks	P	—					—	—	P
Power Overhead Convenience Group — Power Convenience Group, overhead console with compass, ambient temperature and five-function trip computer displays, dual courtesy/reading lamps and sunglasses storage; HomeLink® universal transceiver; and automatic-dimming inside rearview mirror (delete standard dome lamp)	—	O	O				—	—	—
R/T Group — Cloth high-back bucket seats (includes floor console with 12-volt power outlet and premium door trim panels with map pockets), Deluxe Convenience Group, Light Group, fog lamps, body color front and rear bumpers, wheel flares, 17" x 9" chrome/aluminum wheels with matching spare, P255/55R17 BSW Goodyear Eagle LS tires(a), sport suspension, extra-heavy-duty front and rear shock absorbers, heavy-duty rear sway bar and anti-spin differential (2WD only, must have 5.9-liter engine)			—	—	—	—	—	—	S
Skid Plate Group — Fuel tank, transfer case and front suspension skid plates (4WD only)			O	O			O	O	O

(a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.

(b) Except in California.

## REGULAR CAB FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T
<b>EQUIPMENT GROUPS (continued)</b>							
SLT Plus Décor Group — Power Convenience Group, wheel flares, rear stabilizer bar, 16" x 8" cast-aluminum wheels, AM/FM stereo radio with CD and changer controls, remote keyless entry, power door locks, power windows and front floor mats					—	—	—
S	—						
Sport Plus Group — Light Group and Fog Lamps (must have 3.9- or 4.7-liter engine; must have 3.55 or 3.92 axle ratio), wheel flares, rear stabilizer bar, 16" x 8" cast-aluminum wheels, AM/FM stereo radio with CD and changer controls, remote keyless entry, power door locks, power windows and front floor mats						—	—
	—	—	—				S
<b>Tire and Handling Groups</b>							
2WD: P255/65R16 Goodyear Eagle LS outline white letter all-season performance tires, 16" x 8" aluminum wheels with matching spare and rear stabilizer bar (must have 3.55 or 3.92 axle ratio; must have 3.9- or 4.7-liter engine)				—	P	—	P
4WD: P265/70R16 Wrangler RT/S outline white letter all-terrain tires, wheel flares, 16" x 8" aluminum wheels with matching spare and rear stabilizer bar (must have 3.55 or 3.92 axle ratio; must have 3.9- or 4.7-liter engine)				—	P	—	P
	—	P	—	P	—		
Trailer Tow Group — Class IV hitch platform, seven-circuit wiring connector with four-circuit adapter (must have heavy-duty service group and 3.9- or 4.7-liter engine; not available with 2WD)				O	O	O	O



Painted (Gray)		S	—	—	—	—	—	—
Painted (Body Color)			—	S	S	S	—	—
S								
Chrome	—	—	—	—	S	S	—	



range (with automatic transmission), odometer and  
trip odometer      S      S      S      S      S      S      S



with eight Infinity speakers in six locations (late  
availability) — — ○ ○ ○ ○ ○



Spare, Conventional  
S

S S S S S S

(a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.

## CLUB CAB® FEATURE AVAILABILITY

	Base	SXT	Sport	Sport Plus	SLT	SLT Plus	R/T		
<b>POWERTRAIN and CHASSIS (continued)</b>									
Transfer Cases									
NV233HD Electric-shift part-time (4WD only)	S	S	S	—			S	S	S
NV244HD Electric-shift full-time (4WD only; must have 4.7-liter engine and automatic transmission)	O	O	—				—	—	O O
Wheels									
Styled steel, 16" x 7" painted	—	—					S	—	— — — —
Cast-aluminum, 16" x 7"	—				—	—	S	—	S —
Cast-aluminum, 16" x 8" (included in Tire and Handling Groups)	—			P	P		S	P	S —
Cast-aluminum, chrome 17" x 9"	—	S					—	—	— —
<b>SAFETY and SECURITY</b>									
Brake-Shift Interlock (included with automatic transmission)									
	S	S	S	S	S				S S
Restraints									
Air bags: Next-generation front (driver and passenger) with knee bolsters(a)				S	S	S	S	S	S S
Seat Belts									
Front: Height-adjustable three-point seat belts, outboard; lap belt, center	S	S					S	S	S S S
Rear: Three-point belts, outboard; lap belt, center	S	S	S	S	S				S S
Passenger Air Bag On/Off Switch(b)	S	S					S	S	S S S
Security Alarm (includes Sentry Key® engine immobilizer; must have Power Convenience Group)									
	O	—					—	—	O O O
User-Ready Child Seat Tether Anchors — Top, cab back (three)									
	S	S	S	S	S	S	S	S	
Child Seat Anchor System — Lower Anchors and upper Tethers for Children (LATCH)									
	S	S					S	S	S S S
Constant Force Retractors (driver)									
	S	S					S	S	S S S
Interior Upper Head Impact Protection — Front driver and									

passenger (meets 2003 federal standard)

S S S S

S S S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts.

Remember, a back seat is the safest place for children.

(b) Important, always remove key and replace cover. A rearward-facing child seat may be used in the front passenger seat only with the air bag turned off.



- (a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.
- (b) Except in California.

**CLUB CAB® FEATURE AVAILABILITY**

**Base SXT Sport Sport Plus SLT SLT Plus R/T  
EQUIPMENT GROUPS (continued)**

Sport Plus Group — Light Group, fog lamps (must have 3.9- or 4.7-liter engine; must have 3.55 or 3.92 axle ratio), wheel flares, rear stabilizer bar, 16" x 8" cast-aluminum wheels, AM/FM stereo radio with CD and changer controls, remote keyless entry, power door locks, power windows and front floor mats) — — — S

**Tire and Handling Groups**

2WD: P255/65R16 Goodyear Eagle LS outline white letter all-season performance tires(a), 16" x 8" aluminum wheels with matching spare and rear stabilizer bar (must have 3.55 or 3.92 axle ratio; must have 3.9- or 4.7-liter engine) — P O P O P S

4WD: P265/70R16 Wrangler RT/S outline white letter all-terrain tires, wheel flares, 16" x 8" aluminum wheels with matching spare and rear stabilizer bar (must have 3.55 or 3.92 axle ratio; must have 3.9- or 4.7-liter engine) — P O P O P —

Trailer Tow Group — Class IV Hitch Platform, seven-circuit wiring connector with four-circuit adapter (must have Heavy-Duty Service Group and 3.9- or 4.7-liter engine; not available with 2WD) O O O O O O O

(a) Other tire sizes and brands may also be used.

## QUAD CAB™ FEATURE AVAILABILITY

	Sport			
	Sport Plus	SLT	SLT Plus	
<b>EXTERIOR</b>				
Box Bedliner — Under rail		O	O	O
Bumpers				
Front				
Chrome		—	—	S
Painted Black with body color inserts				S
—				
Rear with Step Pads				
Chrome		—	—	S
Painted Black with body color inserts				S
—				
Colors				
Atlantic Blue Pearl Coat, Black, Bright Silver Metallic, Bright White, Flame Red, Graphite Metallic, and Patriot Blue Pearl Coat				O
Dark Garnet Red Pearl Coat and Light Almond Pearl Coat Metallic				O
—				
Defroster — Rear window (includes 6" x 9" heated, folding power outside mirrors; not available with sliding rear window)				O
Fascias, Painted				O
Front and rear (body color)			S	S
Front and rear (Low Gloss Gray)			—	—
Fog Lamps	O	S	O	S
Glass				
Sunscreen, rear door and rear window				S
Tinted, windshield and front door windows				S
S				S
Grille				
Painted, body color		S	S	—
Chrome		—	—	S
Mirrors				
Dual 5" x 7", manual (Black)				S
Dual 5" x 7", power (Black; included in Power Convenience Group)				S
— P — P				S
Dual 5" x 7", power heated fold-away (must have rear defroster)				S
O O O O				S
Moldings				
Side (Black)		—	—	O
Windshield (Black)			S	S

## QUAD CAB™ FEATURE AVAILABILITY

	Sport				Sport Plus SLT			
<b>SLT Plus</b>								
<b>EXTERIOR (continued)</b>								
Paint Treatment								
Monotone	S	S	S	S				
Two-tone, lower		—	—	O	O			
Rear Window — Sliding		O	O	O	O			
Tonneau Cover — Soft		O	O	O	O			
Windshield Wipers — Variable-delay intermittent						S	S	S
S								
<b>INTERIOR</b>								
Assist Handles, Driver and Passenger				S	S	S	S	
Carpet — Front and rear		S	S	S	S			
Cigar Lighter (Smoker's Group – available through Mopar)						O	O	
O	O							
Climate Control — Air conditioning				S	S	S	S	
Colors — Dark Slate Gray and Taupe				O	O	O	O	
Dome Lamp	S	S	—	—				
Floor Mats — Front, carpeted (color-keyed)					O	S	O	S
Instrument Cluster								
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission),								
odometer and trip odometer			S	S	S	S		
Gauges, analog: oil pressure, temperature, voltmeter, tachometer, 110-mph (180-kph)								
speedometer, fuel	S	S	S	S				
Mirror, Rearview — Manual day/night manual					S	S	S	S
Seat and Door Trim — Niagara cloth seats and door trim panel bolsters; door map pockets (color keyed)	S	S	S	S				
Seat and Door Trim — Leather seats and premium door trim panel bolsters; door map pockets (color keyed) (included with Leather Interior Group)						—	P	
—								P
Seats, Front								
40/20/40 cloth split bench with recliners and integral head restraints, right and left; center armrest console with storage (includes floor console with two cup holders and storage bins)	S	S	S	S				
Leather reclining high-back bucket (includes floor console with armrest, covered storage with removable cassette/CD tray, pen holder, coin holder, three cup holders, cellular								

telephone compartment, internal power outlet and lamp); included in Leather Interior Group — P — P

Reclining high-back bucket (includes floor console with armrest, covered storage with

removable cassette/CD tray, pen holder, coin holder, three cup holders, cellular telephone

compartment, internal power outlet and lamp) O O O O

## QUAD CAB™ FEATURE AVAILABILITY

### Sport Sport Plus SLT SLT Plus

#### INTERIOR (continued)

40/20/40 leather split bench with recliners and integral head restraints, right and left;

center armrest console with storage (includes floor console with two cup holders and

storage bins) (must have Leather Interior Group) — O —

O

Power Six-way, Driver — O — O

Seats, Rear — 60/40 split-folding cushion S S S S

#### Sound Systems

AM/FM stereo radio with cassette and four speakers S —

S —

AM/FM stereo radio with cassette, CD, three-band equalizer, 120-watt amplifier with

eight Infinity® speakers in six locations O O O O

AM/FM stereo radio with CD, three-band equalizer, 120-watt amplifier with

eight

Infinity speakers in six locations O S O S

AM/FM stereo radio with in-dash six-disc CD, changer controls, bass and treble controls,

120-watt amplifier with eight Infinity speakers in six locations (late availability)

O O O O

Audio Controls — Steering wheel-mounted, six-function (must have Power Convenience Group, AM/FM stereo radio with cassette and CD and leather-wrapped steering wheel) — O —

O

Steering Column — Tilt (included in Deluxe Convenience Group) —

P — P

#### Steering Wheel

Luxury S S S S

Leather-wrapped (must have Deluxe Convenience Group) —

O — O

Storage Module and Load Floor — Two-compartments, with outboard cup holders and

storage trays S S S S

Sun Visors — Padded cloth with covered mirror, right (color-keyed) S

S S S

#### POWERTRAIN and CHASSIS

##### Brakes, Power

Power four-wheel disc with rear-wheel anti-lock S S S

S

Power anti-lock four-wheel disc                    

Engine Cooling — Heavy-duty (includes auxiliary transmission oil cooler with  
automatic transmission)

## QUAD CAB™ FEATURE AVAILABILITY

	Sport			
	Sport Plus	SLT	SLT Plus	
<b>POWERTRAIN and CHASSIS (continued)</b>				
Tires(a)				
P245/70R16 black sidewall all-season	S	—	S	—
P245/70R16 outline white letter on-off road		—	S	—
S				
P255/55R16 outline white letter all-season (included in 2WD Tire and Handling Group)	P	O	P	—
P265/70R16 outline white letter all-terrain (included in 4WD Tire and Handling Group)	P	—	P	O
Transfer Cases				
NV233HD Electronic-shift part-time (4WD only)			S	S S
S				
NV244 Electronic-shift full-time (4WD only) (must have 4.7- or 5.9-liter engine and automatic transmission)		O	O	O O
Tires(a)				
Cast-aluminum, 16" x 7"		S	—	S —
Cast-aluminum, 16" x 8" (included in Tire and Handling Group)	O	P	O	P
<b>SAFETY and SECURITY</b>				
Brake-Shift Interlock (included with automatic transmission)			S	S
S S				
Restraints				
Air bags: Next-generation front (driver and passenger) with knee bolsters(b)		S	S	S S
Seat Belts				
Front: Height-adjustable three-point seat belts, outboard; lap belt, center	S	S	S	S
Rear: Three-point belts, outboard; lap belt, center			S	S
S S				
Security Alarm (includes Sentry Key® engine immobilizer (must have Power Convenience Group)		—	O	— O
User-Ready Child Seat Tether Anchors — Top, cab back (three)				S
S S S				
Child Seat Anchor System — Lower Anchors and upper Tethers for CHildren (LATCH)		S	S	S S
Constant Force Retractors (driver)			S	S S S
Interior Upper Head Impact Protection — Front driver and passenger; meets 2003 federal standard		S	S	S S

(a) Other tire sizes and brands may also be used.

(b) Certified to federal regulations that allow less forceful air bags. Always use seat belts.

Remember, a back seat is the safest place for children.

## QUAD CAB™ FEATURE AVAILABILITY

### Sport Sport Plus SLT SLT Plus

#### SAFETY and SECURITY (continued)

Deluxe Convenience Group — Automatic speed control and tilt steering column

O S O S

Heavy-Duty Service Group — 136-amp alternator, 750-amp battery, maximum engine cooling

O O O O

Leather Interior Group — Leather and vinyl reclining high-back bucket seats (includes

vinyl door trim bolsters and floor console with armrest, covered storage with removable

cassette/CD tray, pen holder, coin holder, three cup holders, cellular telephone compartment, internal power outlet and lamp; must have Sport Plus Group or SLT

Plus Group, Power Convenience Group, power driver seat and Infinity® speaker system)

— O — O

Power Convenience Group — Power mirrors, remote keyless entry system, power front

windows with driver one-touch open and power door locks

O —

O —

Power Overhead Convenience Group — Power Convenience Group, overhead console with

compass, ambient temperature and five-function trip computer displays, dual courtesy/reading amps, and sunglasses storage; HomeLink® universal transceiver and

automatic-dimming inside rearview mirror

O S O S

Skid Plate Group — Fuel tank, transfer case and front suspension skid plates (4WD Only)

O O O O

SLT Plus Décor Group—Power Convenience Group, Tire and Handling Group, wheel flares,

rear stabilizer bar, 16" x 8" cast-aluminum wheels, AM/FM stereo radio with CD and

changer controls, remote keyless entry, power door locks, power windows and front floor mats

— — — P

Sport Plus Group — Light Group, Fog Lamps (must have 3.9- or 4.7-liter engine; must have 3.55 or 3.92 axle ratio), wheel flares, rear stabilizer bar, 16" x 8" cast-aluminum wheels, AM/FM stereo radio with CD and changer controls, remote keyless entry, power door locks, power windows and front floor mats

— P — —

## QUAD CAB™ FEATURE AVAILABILITY

### Sport

### Sport Plus SLT SLT Plus

#### SAFETY and SECURITY (continued)

##### Tire and Handling Groups

2WD: P255/65R16 Goodyear Eagle LS(a) outline white letter all-season performance

tires, 16" x 8" aluminum wheels with matching spare and rear stabilizer bar

○ S ○ S

4WD: P265/70R16 Wrangler RT/S(a) outline white letter all-terrain tires, wheel flares,

16" x 8" aluminum wheels with matching spare and rear stabilizer bar

○ S ○ S

Trailer Tow Group — Class IV hitch platform, seven-circuit wiring connector with four-

circuit adapter (must have Heavy-Duty Service Group and 3.9- or 4.7-liter engine)

○ ○ ○ ○

(a) Other sizes and brands may also be used.

## SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

### GENERAL INFORMATION

Assembly Plant Dodge City (Warren, Michigan)

Introduction Date October 1999

EPA Vehicle Class Regular Cab, Club Cab® and Quad Cab™ pickup

### ENGINE: 3.9-LITER MAGNUM®, OHV SMPI V-6

Availability Std. — all

Type and Description Six-cylinder, 90° V-type, liquid-cooled

Displacement 239 cu. in. (3906 cu. cm)

Bore x Stroke 3.91 x 3.31 (99.3 x 84.1)

Valve System OHV, 12 valves, roller followers, hydraulic lifters

Fuel Injection Returnless, sequential, multi-port, electronic

Construction Cast-iron block and heads

Compression Ratio 9.1:1

Power (SAE net) 175 bhp (130 kW) @ 4800 rpm (44.9 bhp/L)

Torque (SAE net) 225 lb.-ft. (305 N•m) @ 3200 rpm

Max. Engine Speed 5250 rpm

Fuel Requirement Unleaded regular, 87 octane (R+M)/2

Oil Capacity 4 qt. (3.8L)

Coolant Capacity 14.0 qt. (13.3L)

Emission Controls Dual oxidation mini catalytic converters(b), three-way catalytic converters,

heated oxygen sensors, internal engine features(c)

Estimated EPA Fuel Economy mpg (City/Hwy) 2WD: 16/22 — man. trans., 16/20 — auto. trans.;

4WD: 15/20 — man. trans., 14/18 — auto. trans.

(a) Meets Transitional Low Emission Vehicle (TLEV) requirements in all states.

(b) Used on Regular and Club Cab® to meet Low Emission Vehicle (LEV) requirements in all 50 states. Used on Quad Cab™ to meet Ultra Low Emission Vehicle (ULEV) in California.

(c) Quad Cab meets Tier 1 standards in other 49 states

## SPECIFICATIONS

### ENGINE: 4.7-LITER MAGNUM®, SOHC SMPI V-8

Availability Optional — all models with Sport or SLT equipment

Type and Description V-8, liquid-cooled

Displacement 287 cu. in. (4701 cu. cm)

Bore x Stroke 3.66 x 3.40 (93.0 x 86.5)

Valve System Chain-driven SOHC, 16 valves,  
hydraulic end-pivot roller rockers

Fuel Injection Sequential, multi-port, electronic, returnless

Construction Cast-iron block, aluminum alloy heads

Compression Ratio 9.3:1

Power (SAE net) 235 bhp (175 kW) @ 4800 rpm (49-state Quad Cab)

230 bhp (172 kW) @ 4800 rpm (California Quad Cab, 50-state regular and  
Club Cab)

Torque (SAE net) 295 lb.-ft. (400 N•m) @ 3200 rpm

BHP/Liter 50

Max. Engine Speed 6000 rpm (electronically limited)

Fuel Requirement Unleaded regular, 87 octane (R + M)/2

Oil Capacity 6 qt. (5.7L)

Coolant Capacity 13 qt. (12.3L)

Emission Controls Two oxidation mini catalytic converters(a),

Three-way catalytic converter, heated oxygen sensors, internal engine  
features(b)

Estimated EPA Fuel Economy mpg (City/Hwy) 2WD: 15/20—man. trans., 14/19  
— auto. trans.;

4WD: 14/19—man. trans., 13/18 — auto. trans.

(a) Used on Regular and Club Cab to meet Low Emission Vehicle (LEV)  
standards in all 50 states and on Quad Cab to meet Ultra Low Emission Vehicle  
(ULEV) standards in California.

(b) Cab meets Tier 1 standards in other 49 states.

## SPECIFICATIONS

### ENGINE: 5.9-LITER MAGNUM®, OHV SMPI V-8

Availability Optional — Quad Cab, 2WD Regular Cab with R/T Group and Club Cab with R/T Group

Type and Description Eight-cylinder, 90° V-type, liquid-cooled

Displacement 360 cu. in. (5825 cu. cm)

Bore x Stroke 4.00 x 3.58 (101.6 x 90.9)

Valve System OHV, 16 valves, roller followers, hydraulic lifters

Fuel Injection Sequential, multi-port, electronic

Construction Cast-iron block and heads

Compression Ratio 8.9:1

Power (SAE net) 250 bhp (187 kW) @ 4400 rpm (42.4 bhp/L)(a)

245 bhp (183 kW) @ 4000 rpm (41.5 bhp/L)(b)

Torque (SAE net) 345 lb.-ft. (468 N•m) @ 3200 rpm(a)

335 lb.-ft. (454 N•m) @ 3200 rpm(b)

Max. Engine Speed 5250 rpm

Fuel Requirement Unleaded regular, 87 octane (R+M)/2

Oil Capacity 5 qt. (4.7L)

Coolant Capacity 14.6 qt. (13.7L)

Emission Controls Two oxidation mini catalytic converters(c)(d), three-way catalytic converter,

heated oxygen sensors, internal engine features(e)

Estimated EPA Fuel Economy mpg (City/Hwy) 2WD — 13/17, 4WD — 12/17

(a) With R/T Group only.

(b) Quad Cab™ only.

(c) Meets Low Emission Vehicle (LEV) standards in all states (except Quad Cab).

(d) Quad Cab meets Ultra Low Emission Vehicle (ULEV) standards in California.

(e) Quad Cab meets Tier 1 standards in other 49 states.

## SPECIFICATIONS

### **TRANSMISSION: NV3500 — MANUAL, FIVE-SPEED OVERDRIVE**

Availability Std. with 3.9L and 4.7L engines

Description Synchronized in all gears

Gear Ratios

1st 4.02

2nd 2.32

3rd 1.40

4th 1.00

5th 0.73

Overall Top Gear 2.34 with 3.21 axle, 2.59 with 3.55 axle or 2.86 with 3.92 axle

### **TRANSMISSION: 42RE — AUTOMATIC, FOUR-SPEED OVERDRIVE**

Availability Optional with 3.9L engine

Description Hydraulic control, electronically controlled governor, overdrive lockout and converter clutch

Gear Ratios

1st 2.74

2nd 1.54

3rd 1.00

4th 0.69

Overall Top Gear 2.45 with 3.55 axle or 2.70 with 3.92 axle

### **TRANSMISSION: 46RE — AUTOMATIC, FOUR-SPEED OVERDRIVE**

Availability Included with 5.9L engine

Description Hydraulic control, electronically controlled governor, overdrive lockout and converter clutch

Gear Ratios

1st 2.45

2nd 1.45

3rd 1.00

4th 0.69

Overall Top Gear 2.45 with 3.55 axle or 2.70 with 3.92 axle

## **SPECIFICATIONS**

### **TRANSMISSION: 545RFE—AUTOMATIC, FIVE-SPEED OVERDRIVE**

Availability Optional with 4.7L engine

Description Three planetary gear sets, one overrunning clutch,  
full electronic control, electronically controlled converter clutch

Gear Ratios

1st 3.00

2nd 1.67 — upshift; 1.50 — kick-down

3rd 1.00

4th 0.75

5th 0.67

Overall Top Gear 2.34 with 3.55 axle or 2.59 with 3.92 axle

### **ELECTRICAL SYSTEM**

Alternator 117-amp — std.; 136-amp — opt.

Battery Maintenance-free, 600 CCA — std.; 750 CCA — opt.

### **TRANSFER CASE: NV233HD PART-TIME**

Availability Standard

Shift Mechanism Electrical/electronic

Operating Modes Neutral; 2WD; 4WD High, locked;  
4WD Low, locked

Low Range Ratio 2.72

Center Differential None

### **TRANSFER CASE: NV244 FULL-TIME**

Availability Optional with 4.7L engine and on Quad Cab with 5.9L engines

Shift Mechanism Electrical/electronic

Operating Modes Neutral; 4WD High, full-time; 4WD High, locked;  
4WD Low, locked

Low Range Ratio 2.72

Center Differential Type Planetary with lock

Torque Split, F/R 48/52

## **SPECIFICATIONS**

### **DIMENSIONS and CAPACITIES(a)**

2WD

#### **Regular Cab**

Wheelbase 112.0 (2844)

Track, Front 61.4 (1559.5) with 16 x 7 wheels;  
61.9 (1572) with 16 x 8 and 17 x 9 wheels

Track, Rear 62.4 (1585) with 16 x 7 wheels,  
62.9 (1598) with 16 x 8 and 17 x 9 wheels

Overall Length 196.0 (4980)

Overall Width(a) 71.6 (1819)

Overall Height 66.0 (1677.0)

Tailgate Load Height 29.4 (747.2)

Ground Clearance

Front suspension 9.4 (238)

Rear axle 10.0 (255)

Approach angle 25.0°

Ramp breakover angle 22.5°

Departure angle 20.6°

Fuel Tank Capacity 22 gal. (83L)

(a) All dimensions measured on base model at curb weight with standard tires.

(b) At seating reference point.

## SPECIFICATIONS

### DIMENSIONS and CAPACITIES(a) (CONTINUED)

2WD

#### Club Cab®

Wheelbase 131.0 (3327)  
Track, Front 61.4 (1559) with 16 x 7 wheels  
61.9 (1572) with 16 x 8 and 17 x 9 wheels  
Track, Rear 62.4 (1585) with 16 x 7 wheels  
62.9 (1598) with 16 x 8 and 17 x 9 wheels  
Overall Length 215.1 (5463)  
Overall Width(b) 71.6 (1819)  
Overall Height 66.1 (1680)  
Tailgate Load Height 29.3 (743)  
Ground Clearance  
Front suspension 8.4 (213)  
Rear axle 8.9 (226)  
Approach angle 25.0°  
Ramp Breakover angle 20.5°  
Departure angle 20.5°  
Fuel Tank Capacity 22 gal. (83L)

#### Quad Cab™

Wheelbase 131.0 (3327)  
Track, Front 61.4 (1560) with 16 x 7 wheels  
61.9 (1572) with 16 x 8 wheels  
Track, Rear 62.4 (1585) with 16 x 7 wheels  
62.9 (1598) with 16 x 8 wheels  
Overall Length 215.1 (5463)  
Overall Width(b) 71.6 (1818)  
Overall Height 66.9 (1699)  
Ground Clearance  
Front suspension 9.1 (232)  
Rear axle 9.9 (252)  
Approach angle 25.1°  
Ramp breakover angle 20.5°  
Departure angle 20.5°  
Fuel Tank Capacity 24 gal. (91L)

(a) All dimensions measured on base model at curb weight with standard tires.

(b) At seating reference point.

## SPECIFICATIONS

### DIMENSIONS and CAPACITIES(a) (Continued)

4WD

#### Regular Cab

Wheelbase 112.1 (2848)

Track, Front 61.4 (1560) with 16 x 7 wheels;  
61.9 (1572) with 16 x 8 wheels

Track, Rear 62.4 (1584) with 16 x 7 — std.,  
62.9 (1588) with 16 x 8 wheels — std.

Overall Length 196.0 (4980)

Overall Width(b) 71.6 (1819)

Overall Height 68.6 (1742)

Tailgate Load Height 31.5 (799)

Ground Clearance

Front axle 9.3 (237)

Rear axle 10.3 (262)

Approach angle 31.5°

Ramp breakover angle 19.1°

Departure angle 23.0°

Fuel Tank Capacity 22 gal. (83L)

(a) All dimensions measured on base model at curb weight with standard tires.

(b) At seating reference point.

## SPECIFICATIONS

### DIMENSIONS and CAPACITIES(a) (Continued)

4WD

#### Club Cab®

Wheelbase 131.1 (3331)  
Track, Front 61.4 (1560) with 16 x 7 wheels;  
61.9 (1572) with 16 x 8 wheels  
Track, Rear 62.4 (1585) with 16 x 7 wheels;  
62.9 (1598) with 16 x 8 wheels  
Overall Length 215.0 (5463)  
Overall Width(b) 71.6 (1819)  
Overall Height 68.7 (1745)  
Tailgate Load Height 31.3 (797)  
Ground Clearance  
Front axle 9.4 (239)  
Rear axle 9.9 (2252)  
Approach angle 31.7°  
Ramp breakover angle 17.1°  
Departure angle 22.9°  
Fuel Tank Capacity 22 gal. (83L)  
Frontal Area 28.1 sq. ft. (2.61 sq. m)  
Drag Coefficient 0.467

4WD

#### Quad Cab™

Wheelbase 131.1 (3331)  
Track, Front 61.4 (1560) with 16 x 7 wheels;  
61.9 (1572) with 16 x 8 wheels  
Track, Rear 62.4 (1585) with 16 x 7 wheels;  
62.9 (1598) with 16 x 8 wheels  
Overall Length 215.1 (5463)  
Overall Width(b) 71.6 (1818)  
Overall Height 69.7 (1771)  
Ground Clearance  
Front axle 9.1 (230)  
Rear axle 10.3 (261)  
Approach angle 32.0°  
Ramp Breakover angle 19.5°  
Departure angle 23.3°  
Fuel Tank Capacity 24 gal. (91L)

(a) All dimensions measured on base model at curb weight with standard tires.

(b) At seating reference point.

## SPECIFICATIONS

### CARGO BOX DIMENSIONS

#### Regular and Club Cab® Box

Nominal Box Length, ft. 6.5  
 Length at Floor, Tailgate Closed 77.7 (1975)  
 Width, Maximum 59.3 (1506)  
 Distance Between Wheelhouses 45.1 (1146)  
 Depth 17.5 (446)  
 Volume 46.0 cu. ft. (1.3 cu. m)  
 Tailgate Opening Width 53.3 (1354)

#### Quad Cab™ Box

Nominal Box Length, ft. 5.5  
 Length at Floor, Tailgate Closed 63.7 (1619)  
 Width, Maximum 59.3 (1507)  
 Distance Between Wheelhouses 45.1 (1145)  
 Depth 17.5 (444)  
 Volume 38.1 cu. ft. (1.08 cu. m)  
 Tailgate Opening Width 53.3 (1355)

### ACCOMMODATIONS

	Regular Cab	Club Cab®	Quad Cab™
Seating Capacity, F/R	2 or 3/—	2 or 3/3	2 or 3/3
Front			
Head room	40.0 (1016)	40.0 (1015)	39.6 (1007)
Leg room	41.9 (1063)	41.9 (1063)	41.9 (1063)
Shoulder room	57.2 (1453)	57.2 (1453)	57.2 (1453)
Hip room	54.9 (1395)	54.9 (1395)	55.9 (1420)
Seat travel	8.7 (220)	8.7 (220)	8.7 (220)
Recliner range, degrees	53	53	53
SAE interior volume, cu. ft. (cu. m)	(1.56)	55.5 (1.57)	55.5 (1.57) 54.8
Rear			
Head room —	36.8 (934)	38.2 (972)	
Leg room — min.	—	32.1 (815)	36.0 (914)
Knee clearance	—	-4.6 (-116)	3.0 (77)
Shoulder room	—	54.7 (1389)	57.4 (1459)
Hip room —	53.1 (1349)	54.2 (1376)	
SAE interior volume, cu. ft. (cu. m)	—	37.3 (1.06)	45.8 (1.30)
Cab Cargo Volume			
(Rear seat up), cu. ft. (cu. m)	—	26.0 (0.74)	29.9 (0.85)

## SPECIFICATIONS

### BODY and FRAME

#### 2WD 4WD

Layout	Longitudinal front engine, Hotchkiss drive	Longitudinal front engine, Hotchkiss drive, transfer case
Construction	Ladder-type frame, steel cab, double-wall steel pickup box	Ladder-type frame, steel cab, double-wall steel pickup box

### SUSPENSION

#### 2WD 4WD

Description		
Front	Upper and lower "A" arms, coil springs, torsion bars, gas-charged shock absorbers, stabilizer bar	Upper and lower "A" arms, gas-charged shock absorbers, stabilizer bar
Rear	Live axle, four-leaf longitudinal springs, gas-charged shock absorbers — std.; stabilizer bar — opt. with Tire and Handling Group	Live axle, four-leaf two-stage longitudinal springs, gas-charged shock absorbers — std.; stabilizer bar — opt. with Tire and Handling Group

### STEERING

#### Regular Cab Club Cab® and Quad Cab™

#### 2WD

Type	Power rack and pinion	Power rack and pinion
Overall Ratio	14.7:1	14.7:1
Turning Diameter (curb-to-curb)	36.0 ft. (11.0 m)	41.2 ft. (12.6 m)
Steering Turns (lock-to-lock)	2.86	2.86

#### 4WD

Type	Power rack and pinion	Power rack and pinion
Overall Ratio	16.1:1	16.1:1
Turning Diameter (curb-to-curb)	35.8 ft. (10.9 m)	41.2 ft. (12.6 m)
Steering Turns (lock-to-lock)	3.18	3.18

## **SPECIFICATIONS**

### **BRAKES**

#### Front

Availability Std. — All

Size and type 11.3 x 0.9 (287 x 24) vented disc  
with 2.76 (70) single-piston sliding caliper(a)

Swept area 214 sq. in. (1381 sq. cm)

#### Rear

Availability Std. — All

Size and type 9.0 x 2.5 (229 x 64) disc with ABS

Swept area 141.4 sq. in. (912 sq. cm)

#### Power Assist

Availability Std. — All

Type Tandem-diaphragm vacuum

(a) Available with ABS.

**SPECIFICATIONS**

**TRAILER TOWING(a)**

**Regular Cab 2WD**

GVWR, lbs.(b)	Engine and Transmission	Maximum Trailer		GCWR,
		Axle Ratio	Weight lbs.(d)	
5000	3.9L V-6 and five-speed manual	3.21	7500	3650
		3.55	8000	4150
	3.9L V-6 and four-speed automatic			3.55 8800 4950
		3.92	9200	5350
	4.7L V-8 and five-speed manual	3.55	9500	5300
		3.92	10,500	6300
	4.7L V-8 and five-speed automatic	3.55	9200	5300
	3.92	10,500	6600	
	5.9L V-8 and four-speed automatic(e)	3.92	6090	1800
5900	3.9L V-6 and five-speed manual	3.21	7500	3550
	3.9L V-6 and four-speed automatic			3.55 8000 4050
	4.7L V-8 and five-speed manual	3.55	9500	5600
		3.92	10,500	6600
	4.7L V-8 and five-speed automatic	3.55	9200	5300
	3.92	10,500	6300	

(a) Tongue weight should be 10-15 percent of loaded trailer weight but must not cause vehicle to exceed GVWR or GAWR.

(b) Gross Vehicle Weight Rating.

(c) Maximum Trailer Weight Ratings include cargo and fluids in the trailer and 150 lbs. for the driver and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

(d) GCWR (Gross Combined Weight Rating) is the maximum allowable combined weight of loaded truck and trailer. It includes the weight of passengers, cargo and fuel in the truck and cargo in the trailer.

(e) R/T Equipment Group only.

**SPECIFICATIONS**

**TRAILER TOWING(a) (continued)  
Regular Cab 4WD**

GVWR, lbs.(b)	Engine and Transmission	Maximun Trailer		GCWR,
		Axle Ratio	Weight lbs.(d)	
5400	3.9L V-6 and five-speed manual	3.55	8000	3950
	3.92	8800	4750	
	3.9L V-6 and four-speed automatic	3.92	9200	5100
	4.7L V-8 and five-speed manual	3.55	9500	5400
5900	3.92	10,500	6400	
	4.7L V-8 and five-speed automatic	3.55	9200	5000
	3.92	10,500	6300	
	3.9L V-6 and five-speed manual	3.55	8000	3850
5900	3.92	8800	4650	
	3.9L V-6 and four-speed automatic	3.92	9200	5050
	4.7L V-8 and five-speed manual	3.55	9500	5300
	3.92	10,500	6300	
5900	4.7L V-8 and five-speed automatic	3.55	9200	4950
	3.92	10,500	6250	

(a) Tongue weight should be 10-15 percent of loaded trailer weight but must not cause vehicle to exceed GVWR or GAWR.

(b) Gross Vehicle Weight Rating

(c) Maximum Trailer Weight Ratings include cargo and fluids in the trailer and 150 lbs. for the driver and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

(d) GCWR (Gross Combined Weight Rating) is the maximum allowable combined weight of loaded truck and trailer. It includes the weight of passengers, cargo and fuel in the truck and cargo in the trailer.

(e) R/T Equipment Group only.

**SPECIFICATIONS**

**TRAILER TOWING(a) (continued)**

**Club Cab® 2WD**

GVWR, lbs.(b)	Maximun Trailer		Axle Ratio	GCWR,		
	Engine	Transmission				
lbs.(c)	Weight	lbs.(d)				
5350	3.9L V-6	and five-speed manual	3.21	7500	3500	
			3.55	8000	4000	
	3.9L V-6	and four-speed automatic		3.55	8800	4700
			3.92	9200	5100	
	4.7L V-8	and five-speed manual	3.55	9500	5300	
			3.92	10,500	6300	
	4.7L V-8	and five-speed automatic		3.55	9200	5000
			3.92	10,500	6300	
		5.9L V-8	and four-speed automatic(e)	3.92	6225	1850
	6010(f)	3.9L V-6	and five-speed manual	3.55	8000	3900
			3.92	9200	5050	
4.7L V-8		and five-speed manual	3.55	9500	5300	
			3.92	10,500	6300	
		4.7L V-8	and five-speed automatic		3.55	9200
		3.92	10,500	6300		

(a) Tongue weight should be 10-15 percent of loaded trailer weight but must not cause vehicle to exceed GVWR or GAWR.

(b) Gross Vehicle Weight Rating.

(c) Maximum Trailer Weight Ratings include cargo and fluids in the trailer and 150 lbs. for the driver and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

(d) GCWR (Gross Combined Weight Rating) is the maximum allowable combined weight of loaded truck and trailer. It includes the weight of passengers, cargo and fuel in the truck and cargo in the trailer.

(e) R/T Equipment Group only.

(f) Except with California emissions.

## SPECIFICATIONS

### TRAILER TOWING(a) (continued)

#### Club Cab® 4WD

GVWR, lbs.(b)	Maximun Trailer		Axle Ratio	GCWR,		
	Engine	Transmission				
lbs.(c)	Weight	lbs.(d)				
6010(f)	3.9L V-6	and five-speed manual	3.55	8000	3600	
			3.92	8800	4400	
	3.9L V-6	and four-speed automatic	3.92	9200	4800	
	4.7L V-8	and five-speed manual	3.55	9500	5050	
			3.92	10,500	6050	
4.7L V-8	and five-speed automatic	3.55	9200	4750		
6010(f)	3.9L V-6	and five-speed manual	3.55	8000	3600	
			3.92	8800	4400	
	3.9L V-6	and four-speed automatic	3.92	9200	4800	
	4.7L V-8	and five-speed manual	3.55	9500	5050	
			3.92	10,500	6050	
4.7L V-8	and five-speed automatic	3.55	9200	4750		

(a) Tongue weight should be 10-15 percent of loaded trailer weight but must not cause vehicle to exceed GVWR or GAWR.

(b) Gross Vehicle Weight Rating.

(c) Maximum Trailer Weight Ratings include cargo and fluids in the trailer and 150 lbs. for the driver and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

(d) GCWR (Gross Combined Weight Rating) is the maximum allowable combined weight of loaded truck and trailer. It includes the weight of passengers, cargo and fuel in the truck and cargo in the trailer.

(e) R/T Equipment Group only.

(f) Except with California emissions.

## SPECIFICATIONS

### TRAILER TOWING(a) (continued)

#### Quad Cab™ 2WD

GVWR, lbs.(b) lbs.(c)Weight lbs.(d)	Maximun Trailer Engine and Transmission		Axle Ratio	GCWR,	
6010(e)	3.9L V-6 and five-speed manual	3.55	8000	3600	
	3.92	8800			4400
	3.9L V-6 and four-speed automatic	3.55	8800	4400	
	3.92	9200			4800
	4.7L V-8 and five-speed manual	3.55	9500	5050	
	3.92	10,500			6050
	4.7L V-8 and five-speed automatic	3.55	9200	4750	
	3.92	10,500			6050
	5.9L V-8 and four-speed automatic	3.55	9200	4350	
	3.92	10,800			5950

#### Quad Cab 4WD

GVWR, lbs.(b) lbs.(c)Weight lbs.(d)	Maximun Trailer Engine and Transmission		Axle Ratio	GCWR,	
6010(e)	3.9L V-6 and five-speed manual	3.55	8000	3400	
	3.92	8800			4200
	3.9L V-6 and four-speed automatic	3.55	8800	4200	
	3.92	9200			4600
	4.7L V-8 and five-speed manual	3.55	9500	4800	
	3.92	10,500			5800
	4.7L V-8 and five-speed automatic	3.55	9200	4500	
	3.92	10,500			5800
	5.9L V-8 and four-speed automatic	3.55	9200	4350	
	3.92	10,800			5950

(a) Tongue weight should be 10-15 percent of loaded trailer weight but must not cause vehicle to exceed GVWR or GAWR.

(b) Gross Vehicle Weight Rating.

(c) Maximum Trailer Weight Ratings include cargo and fluids in the trailer and 150 lbs. for the driver and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

(d) GCWR (Gross Combined Weight Rating) is the maximum allowable combined weight of loaded truck and trailer. It includes the weight of passengers, cargo and fuel in the truck and cargo in the trailer.

(e) Except with California emissions.